

Eye and Eye Web Slings

- Eye and Eye slings can be used in choker, vertical and basket hitches.
- Slings with Half Twist (Type 4) eyes are furnished unless Flat (Type 3) eyes are specified.
- Sling eyes will be wrapped at the bearing point unless otherwise specified.
- Eye & Eye nylon & polyester lifting slings featuring flat eyes can be used in all three hitches: choker, vertical and basket.
- Heavy duty nylon rigging slings featuring the Flat Eye and Eye design are made in widths ranging from as narrow as 1 inch and as wide as 12 inches.
- All Lift-It® Flat Eye & Eye slings feature protection at the sling eye bearing points.
- The extra protection wrapped around the sling eye provides additional service life as this is a critical wear area for all polyester and nylon rigging slings.
- Sling eyes are automatically tapered to a narrower width on Eye and Eye lifting slings that are over 3 inches in width.
- At Lift-It they do not charge extra to taper the eyes for your 2 inch wide rigging straps.
- Flat Eye, Eye and Eye nylon lifting slings used by crane and rigging customers around the world provide for the lowest profile eye available.
- Low profile eyes make sling removal easier when tight clearances are unavoidable.
- Nylon rigging slings that feature flat eyes are also referred to as double eye slings or Type 3 slings.
- If a more supple body composition is desired consider using Lift-It® polyester roundslings in the eye and eye style.
- Eye & Eye polyester round slings are formed by passing an exterior sleeve over the strands of the polyester roundsling.



Eye & Eye Web Sling

Width (in)	Stock No.	Eye Dimensions (in)		Working Load Limit (lb)					Sling Weight (lb)		Minimum Sling Length (ft)
		Width (in)	Length (in)	Choker	Vertical	Basket Hitches			Base 8ft	Adder/ft	
						90°	60°	45°			
1	EE1-901P	1	9	1,200	1,600	3,200	2,770	2,260	0.67	0.05	4
1	EE2-901P	1	9	2,500	3,200	6,400	5,540	4,520	1.00	0.11	3
2	EE1-902P	2	12	2,500	3,200	6,400	5,540	4,520	1.34	0.11	4
2	EE2-902P	2	12	5,000	6,400	12,800	11,080	9,050	2.02	0.22	4
3	EE1-903P	1-1/2	12	3,800	4,800	9,600	8,310	6,780	2.29	0.18	4
3	EE2-903P	1-1/2	12	7,000	8,860	17,720	15,340	12,530	3.24	0.35	4
3	EE4-903P	1-1/2	18	13,000	17,000	34,000	29,440	24,040	6.60	0.70	5
4	EE2-904P	1-1/2	14	9,000	11,400	22,800	19,740	16,120	3.96	0.44	5
4	EE4-904P	2	18	18,000	22,800	45,600	39,480	32,240	8.36	0.88	6
6	EE4-906P	3	24	24,000	30,000	60,000	51,960	42,420	12.31	1.30	8

Available in either nylon or polyester webbing. Polyester comes standard on all models. Polyester webbing is available in (9) heavy web class only. For Polyester Max Edge™ webbing add letters "PME" to Stock Number. Consider using Twin-Path® Extra Slings in applications requiring 4 ply thick slings, wider than 6 inches.

DO NOT EXCEED WORK LOAD LIMITS



- Can fail if damaged, misused, or overloaded.
- Inspect before each use.
- Use by untrained personnel is hazardous.
- OBSERVE and DO NOT EXCEED WORKING LOAD LIMITS.
- DEATH and INJURY can occur from improper use or maintenance.



For complete warning and application information from Lift-It, scan the QR code.

