

HARDWARE CHAIN

Grade 43 High Test Chain (NACM)

Grade 43 Chain features both high tensile strength and resistance to wear needed by modern hauling and heavy duty trucking, farm and construction firms. Working load limits exceed those of ordinary low carbon or general utility chain. Order unit is foot.

NOT FOR OVERHEAD LIFTING



Full Drum

Stock #			Trade Size		Wire Dia. (In.)	Inside Link Dim. (Inches)		Ft. Per Drum	Net Wt. (Lbs.)	Working Load Limit	
Self-Colored	Zinc	HDG	In.	MM		Length (Nominal)	Width (Nominal)			Lbs.	Kgs.
5031213	5031233	5630247	1/4	7	0.274	1.236	0.491	800	508	2,600	1,180
5031313	5031333	5630347	5/16	8	0.328	1.285	0.493	550	512	3,900	1,770
5031413	5031433	5630447	3/8	10	0.392	1.374	0.567	400	544	5,400	2,450
5031613	5031633	5630647	1/2	13	0.509	1.782	0.770	200	460	9,200	4,174
5030813	---	5630847	5/8	16	0.625	2.016	0.876	150	554	13,000	5,897
5030913	---	5030947	3/4	20	0.781	2.613	1.020	100	542	20,200	9,163
5031013	---	5031047	7/8	22	0.906	2.661	1.261	75	582	24,500	11,113
5301113	---	5301147	1	26	1.031	2.878	1.432	60	606	30,000	13,608

Half Drum

Stock #			Trade Size		Wire Dia. (In.)	Inside Link Dim. (Inches)		Ft. Per Drum	Net Wt. (Lbs.)	Working Load Limit	
Self-Colored	Zinc	HDG	In.	MM		Length (Nominal)	Width (Nominal)			Lbs.	Kgs.
5031214	5031234	5630248	1/4	7	0.274	1.236	0.491	400	254	2,600	1,180
5031314	5031334	5630348	5/16	8	0.328	1.285	0.493	275	256	3,900	1,770
5031414	5031434	5630448	3/8	10	0.392	1.374	0.567	200	272	5,400	2,450
5031614	5031634	5630648	1/2	13	0.509	1.782	0.770	100	230	9,200	4,174

5 Gallon Square Pail

Stock #	Trade Size		Wire Dia. (In.)	Inside Link Dim. (Inches)		Ft. Per Pail	Net Wt. (Lbs.)	Working Load Limit	
Self-Colored	In.	MM		Length (Nominal)	Width (Nominal)			Lbs.	Kgs.
5431215	1/4	7	0.274	1.236	0.491	150	96	2,600	1,180
5431315	5/16	8	0.328	1.285	0.493	100	93	3,900	1,770
5431415	3/8	10	0.392	1.374	0.567	75	102	5,400	2,450

